



HOLDER OPTIONS



SafetyPac™

- Plastic molded insert organizes the Kit elements allowing for quick, easy access
- Translucent material facilitates quick, accurate inspection of Kit contents



SafetyVest™

- Highly reflective strips located on front and back provide maximum visibility
- Flame and heat retardant coated fiberglass fabric withstands temperatures up to 550° F
- Provides extensive surface area protection of the anterior and posterior torso from heat and flame
- One easy-to-use Velcro® strap securely fastens the vest, keeping the user's hands free
- Elastic straps firmly hold Kit contents and provide rapid access

COMPONENTS LIST



EVAC-U8™ Smoke Hood

Catalyst Filter

- Valve System prevents re-breathing of exhaled air (carbon dioxide)
- Multi-stage catalytic filter provides superior protection against toxic gases from fire, including CO
- An electro-statically charged N95 fiber filter traps soot particles that are 0.5 micron and larger
- Mil-spec (military specification) activated carbon charcoal filter absorbs various toxic fumes
- "Zeolite" molecular sieve layer absorbs moisture and toxic gases
- "Hopacalite" catalytic converter changes toxic CO to non-toxic CO₂ and provides up to 15 minutes of protection at 2,500 PPM
- Tested by an independent testing laboratory (Miller-Nelson) and verified by Underwriters Laboratories of Canada
- Provides up to 15 minutes of protection against high concentrations of typical gases found in fire including CO, hydrogen cyanide, hydrogen chloride and acrolein

Teflon®-Coated Kapton® Hood

- Provides transient heat protection up to 800° F
- Chemical resistive properties
- Easily adjustable to fit users of all sizes
- Unlimited field of vision
- Positive-pressure design minimizes potential for toxic gases to enter the hood
- Photo luminescent locator disc
- Manufacturer certified under ISO 9001
- 5-year shelf life



Personal Alarm

- 110-120 decibel continuous sounding alarm
- Run Time: Up to 16 hours of continuous use
- Easy to use ON/OFF switch
- Extremely durable construction
- Battery Type: (2) AAA alkaline batteries (7-yr. non-use shelf life)
- Secure the alarm to a belt or SafetyVest via a clip or around the neck using a lanyard
- Water resistant construction



Sterile Water Packets

- US Coast Guard approved
- No oxygen transfer, will remain usable for up to 5 years
- Withstands temperatures from -40° F to +210 F
- 4.225 ounces of sterile, purified water
- Use for flushing the eyes, drinking or to clean a wound
- 5-year shelf life



Streamlight® 2AA Flashlight

- High-intensity xenon gas filled bi-pin bulb
- Tested candlepower up to 3,500
- Non-conductive and corrosion-proof
- Shock-resistant engineering grade polymer case with thermoplastic elastomer grip
- Unbreakable polycarbonate lens
- Dual switches (head and tailcap)
- Waterproof to 200 feet
- UL listed (Class I, Division 1, 2, Class II, Division 2, Class III)
- c UL listed (Class I, II, Division 2, Class III)
- MSHA approved
- CE approved: meets applicable European Community Directives
- Run time: up to 4 hours of continuous use
- Color: yellow
- Battery type: (2) AA alkaline (7-year non-use shelf life)



12-hour Light Stick

- Illumination for 12 hours
- No heat generated; No sparks
- Non-flammable and non-explosive
- Waterproof
- Withstands drastic environmental changes
- 360° light generation
- Easy to activate