

Technical Specifications

System Requirements

Operating systems	DOS, Windows (3x, 9x, ME, NT4, 2000, XP, 2003 Server and later), Linux, UNIX, HP UX, QNX, SGI, FreeBSD, BeOS, Open VMS, Novell 3.12-6, Solaris, Java Desktop System
Resolution	1600x1200 @75Hz
User to server distance	200m/660ft
System Cable	CAT5, CAT6, CAT7
Operating Temperature	0°C to 40°C / 32°F to 104°F
Storage Temperature	-40°C to 40°C / -40°F to 104°F
Security	Password, multiple-user profiles
Management	AIM (Advanced Integrated Management), RS-232 Control software
Mouse Support	PS/2, Wheel mouse, 5-button mouse, Microsoft intellimouse
Warranty	3 Years

Type	DX Central Unit	DX User Unit	DXU IP
Cables/Connectors	Computer Ports-32 RJ45 Users Port - 4/8 RJ45 Serial Ports - 2 X DB9 LAN - RJ45 Power	System - RJ45 Local Console and CPU KVM + Serial Video - HDD15 Keyboard/Mouse - MiniDin6 Serial - 2 X DB9 Power 2XUSB (Future Application)	System - RJ45 Local Console and CPU KVM + Serial Video - HDD15 Keyboard/Mouse - MiniDin6 Serial - 2 X DB9 Power 2XUSB (Future Application) LAN - RJ45
Rack Mountable		Yes	
Dimensions	43.2x27x4cm / 17x11x1.6"	21.6x27x4 / 8.5x11x1.6"	43.2x27x4 / 17x11x1.6"
Power Consumption		100 - 250 VAC 50/60 Hz	

X RICC

	RICC PS/2 for DX System	X RICC PS/2	X RICC SUN	X RICC USB	X RICC RS232
Server to DX Central Distance	10m/33ft			100m/330ft	
Cables/Connectors			System - RJ45 Video - HDD15 Keyboard/Mouse		Power - Jack
	MiniDin6		MiniDin8	USB	Power - Jack
Rack Mountable			Yes		
Power Supply	From Keyboard		From USB		Power Adapter
Dimensions	24x91x41 mm / 0.94x3.58x1.61"		24x91x41 mm / 1.05x3.58x1.77"		