

System	
Number of Remote units	63
System Cable	CAT5 FTP 2x4x24 A WG Solid Wire
Maximum Distance	110m/360ft
Resolution	Up To 1600x1200@75Hz
Mouse Support	PS/2, Wheel mouse
Operating Systems	DOS, Windows (3x, 9x, 2000, NT4, ME, XP), LINUX, UNIX, HP UX QNX, SGI, FreeBSD, BeOS, Open VMS, NOVELL 3.12-6
Management	On Screen Display (OSD), RS-232 Control Software
Security	Password, multiple user Profiles
Scan	Automatically view all screens at adjustable intervals from 5-995 seconds
Operating Temperature	0° to 40°C/104°F
Storage Temperature	-40°C to 40°C/-40°F to 104°F
Warranty	3 years

Manager Unit		
Type	UPM	MX II
Cables/Connectors	CPU Cable-3 in 1 Screen-HDD15M KB-MiniDin6M Mouse-MiniDin6M System Out-RJ45 Service-RJ11 RS232-DB9	CPU Cable-3 in 1 Screen-HDD15M KB-MiniDin6M Mouse-MiniDin6M System Out-RJ45 Service-RJ11 RS242-DB9 Second User-RJ45

Rack Mountable	Yes
Dimensions	41.5Hx180Dx204.5Lmm / 1.63Hx7.09Dx8.05L" 41.5Hx180Dx226Lmm / 1.63Hx7.09Dx8.90L"
Power Consumption	100-240 VAC 600mA

Remote Unit				
Type	Specter II PS/2	Specter II SUN	Specter II USB	Specter II RS232
Cables/Connectors	VGA-HDD15M KB-MiniDin6M Mouse- MiniDin6M System In/Out RJ45	VGA-HDD15M KB/Mouse- MiniDin8M System In/Out RJ45	VGA-HDD15M KB/Mouse-USB System In/Out RJ45	Data-DB9F Power-USB System In/Out RJ45
Dimensions	28Hx45Dx86Lmm/1.10Hx1.77Dx3.39L"			
Weight	260g/0.57lb			
Shipping Weight	800g/1.76lb			
Power Consumption	From KB/Mouse port 5VDC 300mA	From KB/Mouse port 5VDC 300mA	From KB/Mouse port 5VDC 300mA	From USB port/PS/2 with adapter/ Ext.P.S. with adapter 5VDC 300mA