

Technical Specifications

Operating System	Host Computer: DOS, Novel, Linux, Windows 98, ME, 2000, XP and later Client Computer: Windows 98, ME, 2000, XP and later, Linux, Internet browser with full Java support 2003 Server MAC, UNIX, SAI
Resolution	Local Computer: Up to 1600x1200 @60Hz Remote Computer: Recommended resolution should be higher than resolution on local computer
Number of Remote Units	64
Maximum Distance	110m/360ft
Connection Type	RJ45 - LAN, Autosensing 10/100 Mbit/s RJ45 - 2nd user CAT 5 FTP Cable 2xRJ45 - System (Specters) DB9 - COM1 for initial configuration and external modem DB9 - COM2 for power management only DB9 - RS-232 applications RJ11 - Service HDD15/MiniDIN6 - Local CPU connection MiniDIN6 - User KVM Connection (cable supplied with system)
Shipping Weight	2 kg/4.4 lb
Product Weight	1.5 kg/3.3 lb
Dimensions	431mm x 176mm x 41.5mm / 17 x 6.9 x 1.61in
Power Supply	85 - 265 VAC 50 / 60 Hz
Warranty	3 years
Operating Temperature	5°C to 40°C/41°F to 104°F

Ordering Information

Description	Order No.
Phantom MXIP	0SU21023
Universal Phantom Manager	0SU52015
Phantom Specter II PS/2	0SU51012
Phantom Specter II USB / SUN USB	0SU51011
Phantom Specter II SUN	0SU51013
Phantom Specter II RS232	0SU51014
Rack Mounting Plate (Supplied with the system)	5AC00202