

Technical Specifications

System

Number of Remote units	63
System Cable	CAT5 FTP 2x4x24 AWG Solid Wire
Maximum Distance	110m/360ft
Resolution	Up To 1600x1200@75Hz
Mouse Support	PS/2, Wheel mouse, 5-Button mouse, Microsoft Intellimouse
Operating Systems	DOS, Windows (3x, 9x, 2000, NT4, ME, XP and later), LINUX, UNIX, HP UX, QNX, SGI, FreeBSD, BeOS, Open VMS, Novell 3.12 - 6, SUN Solaris
Management	On Screen Display (OSD), RS-232 Control Software
Security	Password, multiple user profiles
Scan	Automatically view all screens at adjustable intervals from 5-995 seconds
Operating Temperature	0° C to 40°C/32° F to 104°F
Storage Temperature	-40°C to 40°C/-40°F to 104°F
Warranty	3 years

Manager Unit

Type	Universal Phantom Manager (UPM)
Cables & Connectors	CPU Cable - 3 in 1 Screen - HDD15F Keyboard - MiniDin6F Mouse - MiniDin6F System Out - RJ45 Service - RJ11 RS232 - DB9M
Rack Mountable	Yes
Dimensions	41.5Hx180Dx204.5Wmm / 1.63Hx7.09Dx8.05W"
Power Consumption	85-265 VAC 600mA

Remote Unit

Type	Specter PS/2	Specter II SUN	Specter II USB	Specter II RS232
Cables/Connectors	VGA-HDD15M KB-MiniDin6M Mouse-MiniDin6M System In/Out RJ45	VGA-HDD15M KB/Mouse- MiniDin8M System In/Out RJ45	VGA-HDD15M KB/Mouse-USB System In/Out RJ45	Data-DB9F Power-USB System In/Out RJ45
Dimensions	28Hx45Dx86Wmm/1.10Hx1.77Dx3.39W"			
Weight	260g/0.57lb			
Shipping Weight	800g/1.76lb			
Power Consumption	From KB port 5VDC 250mA	From KB/Mouse port 5VDC 300mA	From KB/Mouse port 5VDC 300mA	From USB port/PS/2 with adapter/ Ext. P.S. with adapter 5VDC 300mA