

17" TFT RACK MOUNT MONITOR



- Mounts in 7U of rack space.
- Analog and Digital inputs.
- Wide viewing angles and fast response.
- High contrast ratios for excellent picture quality.
- 17" TFT LCD display with 1280 x 1024 resolution.
- Steel front panel construction with a durable powder coat finish.

GENERAL SPECIFICATIONS

Dimensions:

19.0" (W) x 12.25" (H) x 2.5" (D)

Weight:

8.5 lbs.

Power:

100 - 240 VAC, 50/60 Hz.
38 Watts max.

On-Screen Controls:

Brightness, Contrast, Horizontal & Vertical
Position, Auto Adjust, OSD H & V Position, Input Select
Color Temp., Reset.

Plug & Play:

DDC1 and DDC2B

Temperature:

Operating: 10°C to 40°C
Storage: -20°C to 45°C

Humidity:

Operating: 10 to 80% RH (max)

Input Signal (VGA):

R.G.B. analog video, TTL H & V sync.

Input Signal (Digital):

DVI-D (TDMS).

Input Connectors:

Analog: 15-pin mini D-Sub.
Digital: 24 pin DVI-D.

Colors Available:

Black.

DISPLAY SPECIFICATIONS

Display Type:

Active matrix TFT LCD

Display area:

17" Diagonal.

Colors Displayed:

16.2 million colors.

Contrast Ratio:

500:1

Brightness:

270 cd/m² typ.

Viewing Angle (CR>5):

Horizontal (L/R): 75° / 75°
Vertical (U/D): 60° / 75°

Response Time:

<12 ms

Resolution:

VGA up to 1280 x 1024.

Horizontal Frequency:

30 to 81 KHz.

Vertical Frequency:

56 to 75 Hz.

Specifications subject to change without notice.

MODEL NUMBER

RMM-407N



RECORTEC, INC.