

1U 15" OR 17" TFT RACK MOUNT MONITOR



- Mounted with included smooth action ball bearing slides which lock in the extended position.
- Display powers off preserving back light life when tilted down for sliding into the rack.
- Retainer and lock options to keep unit contained in the rack when not in use.
- Housed in rugged steel construction with a durable powder coat finish.
- Display surface protected by a clear unbreakable Lexan™ covering.

GENERAL SPECIFICATIONS

Dimensions:

RMM-605: 19.0" (W) x 1.75" (H) x 19.0" (D)
 RMM-607: 19.0" (W) x 1.75" (H) x 19.0" (D)

Weight:

27 lbs

Power (TFT Display):

90 - 260 VAC, 50/60 Hz.
 60 Watts maximum

On-Screen Controls:

Brightness, Contrast, Horizontal & Vertical
 Position, Auto Adjust, OSD H & V Position, Load
 and Save Values

Plug & Play:

DDC1 and DDC2B

Temperature:

Operating: 0°C to 50°C
 Storage: -20°C to 60°C

Humidity:

Operating: 10 to 85% RH (max)

Input Signal (VGA):

R.G.B. analog video, TTL H & V sync.

Input Connector:

Display: 15-pin mini D-Shell

Colors Available:

Choice of Black (B) or Light Gray.
 Specifications subject to change without notice.

DISPLAY SPECIFICATIONS

Display Type:

Active matrix TFT LCD

Colors:

16.7 million colors

Contrast Ratio:

RMM-605: 400:1 typ.
 RMM-607: 1000:1 typ.

Brightness:

RMM-605: 250 cd/m² typ.
 RMM-607: 280 cd/m² typ.

Viewing Angle:

17" 15"
 Horizontal: 178° 130°
 Vertical: 178° 100°

Response Time:

25ms.

Resolution:

640 x 350
 640 x 480
 800 x 600
 1024 x 768
 1280 x 1024 (17")

Display Area:

15" - 15" Diagonal
 17" - 17" Diagonal

Horizontal Frequency:

15" - 31.47 to 68 KHz
 17" - 31.5 to 80 KHz

Vertical Frequency:

15" - 60 to 85 Hz
 17" - 56 to 75 Hz.

MODEL NUMBER

RMM-60(X)(X)(X)

15" TFT Display = 5

17" TFT Display = 7

Blank = Standard Front Panel

R = Front Panel + Retainer Screws

L = Front Panel + Lock

C = Front panel + Lock + Retainer Screw

Blank = Light Gray

B = Black



RECORTEC, INC.