



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: OMNISMART700

### OmniSmart UPS System - Line-interactive battery backup for personal PCs and workstations



#### Highlights

- 700VA line interactive tower UPS
- Maintains 120V nominal output over an input range of 75 to 147V
- Workstation optimized features include USB port (HID-PDC compliant), single line TEL / DSL line surge suppression and three surge-only outlets
- Input: NEMA 5-15P (120V 15A) / Output: 6 NEMA 5-15R (120V)
- 2 year product warranty / \$200,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

#### Description

Tripp Lite's OMNISMART700 line-interactive UPS system offers voltage regulation, surge suppression and long-lasting battery support for personal computers, internetworking equipment and other sensitive electronics. Supports entry-level PC systems for up to 45 min. during power failures so that connected equipment can be shut down without data loss. Automatic voltage regulation (AVR) circuits regulate brownouts as low as 75V and overvoltages as high as 147V back to normal 120V levels without consuming battery power. Offers complete desktop power protection in an attractive black upright tower configuration. Includes 3 battery-supported outlets for computer, monitor and one vital system peripheral, plus 3 additional surge suppression-only outlets for printers and other system accessories not requiring battery support. DB9 port and HID-compliant USB port enable optional unattended system shutdown without data loss in the case of extended power failure, cabling included. HID-compliant USB port enables integration with built-in power management and auto shutdown features of Windows and Mac OS X. PowerAlert software available via free download from [www.tripplite.com](http://www.tripplite.com). Built-in dataline protection jacks offer protection of a single dialup tel/DSL line or network Ethernet connection. Built-in audible alarm and 4 front panel LEDs indicate line power status, battery power status, battery low/replace status and overload. 700VA/450W power-handling ability supports entry-level PCs, network workstations, point-of-sale equipment, small business phone systems, audio/video equipment and home theater systems. Provides 4 min. battery runtime with a full load of 700VA/450W and 17 min. with a half load of 350VA/225W. Supports user battery replacement via built-in access panel. 2-year warranty; \$200,000 [connected equipment insurance](#) (USA & Canada only).

#### Package Includes

- OMNISMART700 UPS System
- DB9, USB and telephone interconnection cables
- Instruction manual with warranty information

#### Features

- OMNISMART700 line-interactive UPS system offers voltage regulation and battery support, plus complete AC and tel/DSL/Ethernet line surge suppression
- Supports entry-level PC systems for up to 45 min. during power failures to enable safe system shutdown
- Supports a full load of 700VA/450W for 4 min. and a half load of 350VA/225W for 17 min.
- Automatic voltage regulation (AVR) circuits correct brownouts as low as 75V and overvoltages as high as 147V back to normal 120V levels without consuming battery power
- Attractive black tower configuration
- Includes 6 NEMA 5-15R outlets: 3 battery-supported and 3 surge suppression-only outlets. 6-ft. AC line cord with NEMA 5-15P plug

- DB9 port and HID-compliant USB port enable unattended shutdown without data loss during extended power failures; complete cabling included
- Built-in communications ports support on battery, low battery, power restored, AC line voltage, DC battery voltage and battery capacity messaging; interface supports timed inverter shutoff after unattended shutdown, activate self-test and 10-sec. reboot of connected equipment
- HID-compliant USB port enables integration with built-in power management and auto shutdown features of Windows and Mac OS X
- PowerAlert UPS monitoring and unattended shutdown software available via free download from [www.tripplite.com](http://www.tripplite.com)
- Supports Tripp Lite's WatchDog software application to restore unresponsive programs by automatically restarting them and rebooting completely locked computers by automatically switching UPS power off and back on again (part # WATCHDOGSW)
- Built-in dataline suppression jacks protect a single dialup tel/DSL line or network Ethernet line connection
- Built-in audible alarm and 4 front panel LEDs indicate UPS system and line power status
- 700VA/425W power-handling ability supports a variety of computer, internetworking, telecom and consumer electronics equipment
- Supports hot-swap battery replacement via built-in access panel
- Compatible with 120V/60Hz applications for USA, Canada, Mexico and more
- 2-year warranty
- \$200,000 [connected equipment insurance](#) (USA & Canada only)

## Specifications

OUTPUT	
Output Volt Amp Capacity (VA)	700
Output Watt Capacity (watts)	450
Nominal Output Voltage(s) Supported	115V; 120V
Frequency compatibility	60 Hz
Output voltage regulation (line mode)	-18%, +8%
Output voltage regulation (Battery mode)	115V (+/- 5%)
Built-in UPS output receptacles	6 5-15R outlet(s)
Surge suppression only outlets	3 UPS outlets, 3 surge-only outlets
Output AC waveform (AC mode)	Sine wave
Output AC waveform (battery mode)	PWM sine wave
INPUT	
Rated input current (at maximum load)	12A
Nominal Input Voltage(s) Supported	120V AC
UPS input connection type	5-15P
UPS Input cord length (ft.)	6
UPS Input cord length (m)	1.8

<b>Recommended Electrical Service</b>	15A 120V
<b>Input cord length (ft.)</b>	6
<b>Input cord length (m)</b>	1.8
<b>BATTERY</b>	
<b>Full load runtime (minutes)</b>	4 min. (450w)
<b>Half load runtime (minutes)</b>	17 min. (225w)
<b>DC system voltage (VDC)</b>	12
<b>Battery recharge rate (included batteries)</b>	Less than 4.5 hours from 10% to 90%
<b>Replacement battery cartridge (internal UPS battery replacement)</b>	RBC51
<b>Battery Access</b>	Battery access door
<b>Battery replacement description</b>	Hot-swappable, user replaceable batteries
<b>VOLTAGE REGULATION</b>	
<b>Voltage regulation description</b>	Automatic voltage regulation (AVR) maintains line power operation with an input voltage range of 75 to 147
<b>Overvoltage correction</b>	Input voltages between 128 and 147 are reduced by 12%
<b>Undervoltage correction</b>	Input voltages between 93 and 107 are boosted by 14%
<b>Severe undervoltage correction</b>	Input voltages between 75 and 92 are boosted by 30%
<b>LEDS ALARMS &amp; SWITCHES</b>	
<b>LED Indicators</b>	4 LEDs indicate line power, battery power, overload and battery low/replace status
<b>Alarms</b>	Audible alarm indicates power-failure and low-battery conditions
<b>Alarm cancel operation</b>	Power-fail alarm can be silenced using alarm-cancel switch; once silenced, alarm will re-sound to indicate low-battery status
<b>Switches</b>	2 Switches control off/on power status and alarm-cancel/self-test operation
<b>SURGE / NOISE SUPPRESSION</b>	
<b>UPS AC suppression joule rating</b>	510
<b>UPS AC suppression response time</b>	Instantaneous
<b>UPS Dataline suppression</b>	1 line TEL / DSL or 10Base T Ethernet protection
<b>EMI / RFI AC noise suppression</b>	Yes
<b>AC suppression joule rating</b>	510

AC suppression response time	Instantaneous
Dataline suppression	1 line TEL / DSL or 10Base T Ethernet protection
<b>PHYSICAL</b>	
Installation form factors supported with included accessories	Tower
Installation form factors supported with optional accessories	Wallmount (use <a href="#">UPSWM</a> - tower mounting kit)
Primary form factor	Tower
UPS / Power Module dimensions in primary form factor (height x width x depth / inches)	10.8 x 5.2 x 7.5
UPS / Power Module dimensions in primary form factor (height x width x depth / cm)	27.3 x 13.3 x 19
UPS / Power Module weight (lbs)	20
UPS / Power Module weight (kg)	9.1
UPS Shipping dimensions (height x width x depth / inches)	14 x 8.2 x 10.4
UPS Shipping dimensions (height x width x depth / cm)	35.6 x 21 x 26.4
Shipping weight (lbs)	22
Shipping weight (kg)	10
UPS housing material	PVC
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
Storage Temperature Range	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
Relative Humidity	0 to 95%, non-condensing
AC mode BTU / hr. (full load)	47.3
Battery mode BTU / hr. (full load)	431.5
Audible Noise	
<b>COMMUNICATIONS</b>	
Communications interface	USB (HID enabled); DB9 Serial
PowerAlert software	Free download from <a href="http://www.tripplite.com">www.tripplite.com</a>

<b>Communications cable</b>	USB and DB9 serial cabling included
<b>WatchDog compatibility</b>	Supports Watchdog application, OS and hard-reboot restart options for remote applications
<b>LINE / BATTERY TRANSFER</b>	
<b>Transfer time</b>	2-4 milliseconds
<b>Low voltage transfer to battery power (setpoint)</b>	75
<b>High voltage transfer to battery power (setpoint)</b>	147
<b>SPECIAL FEATURES</b>	
<b>Cold Start (startup in battery mode during a power failure)</b>	Cold-start operation supported
<b>High availability UPS features</b>	Hot swappable batteries
<b>Green &amp; high efficiency features</b>	Greater than 95% efficiency - GREEN UPS (logo); Line interactive UPS with severe brownout and overvoltage correction
<b>CERTIFICATIONS</b>	
<b>UPS Certifications</b>	Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico); Meets FCC Part 15 Category B (EMI); Meets FCC Part 68 / Industrie Canada (telecommunications); ROHS (Reduction of Hazardous Substances)
<b>WARRANTY</b>	
<b>Product Warranty Period (U.S., Canada &amp; Puerto Rico)</b>	2 years
<b>Connected Equipment Insurance (U.S., Canada &amp; Puerto Rico)</b>	\$200,000 connected equipment insurance

## Related Items

### Optional Products

Product Type	Related Model	Description	Qty.
USB Hubs/Accessories	<a href="#">U022-010</a>	10-ft. USB2.0 A/B Gold Device Cable (A Male to B Male)	-
Wallmount Bracket	<a href="#">UPSWM</a>	Wallmount Bracket and installation accessories (4 washers, 4 screws, 1 Velcro safety strap)	-
Software	<a href="#">WATCHDOGSW</a>	WatchDog Service Monitoring / Reboot Software	-
Surge Protectors	<a href="#">DNET1</a>	Network Surge Suppressor - Essential protection for data and communication lines	-
Surge Protectors	<a href="#">DTEL2</a>	Network Surge Suppressor - Essential protection for data and communication lines	-
Extended Warranties	<a href="#">WEXT3-OMNI</a>	3-Year Extended Warranty - For OmniSmart, OmniPro, OmniVS	-
Extended Warranties	<a href="#">WEXT5-OMNI</a>	5-Year Extended Warranty - For OmniSmart, OmniPro, OmniVS	-

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=23](http://www.tripplite.com/en/products/model.cfm?txtModelID=23).

---

Copyright © 2010 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.