



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SU5000RT4UTF

### SmartOnline E-series UPS System - High efficiency, On-line, double-conversion UPS

#### Highlights



- 5kVA / 5000VA / 4500 watt on-line double-conversion extended-run 6U rack/tower UPS configuration
- Supports 208V and 120V nominal output with 2% output voltage regulation
- Zero transfer time, double-conversion and high efficiency economy mode operation supported
- Built-in USB, RS232 and EPO ports, plus support for SNMP/Web and contact-closure accessory card options
- Front panel LEDs and LCD display with scroll-buttons offer detailed UPS and power status information
- Expandable runtime with optional BP192V12-3U external battery packs
- L6-30P input plug / L6-30R, L6-20R and 5-15/20R output receptacles
- \$250,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

#### Description

Tripp Lite E-series SU5000RT4UTF 5000VA / 5kVA / 4500 watt on-line, double-conversion UPS system offers complete power protection for critical server, network and telecommunications equipment in a 6U rack/tower configuration. Full-time active power conditioning provides clean, continuous dual-conversion AC output free of voltage fluctuations, power interruptions and line noise. Fault-tolerant auto-bypass prevents unexpected service interruptions during UPS overload or internal fault conditions. 4U UPS power module with internal batteries and 2U step-down transformer installs in a total of 6 rack spaces (6U) with a maximum installed depth of only 20.75 in. / 52.7 cm. Maintains full-time sine wave output within 2% of 208 and 120V nominal during brownouts as low 100V and overvoltages as high as 300V. Expandable runtime is supported with optional BP192V12-3U external battery packs. Battery independent restart ensures automatic UPS power-up without user interaction after lengthy power outages, even when batteries are expired and require replacement. Double-conversion operation converts raw input from AC to DC, then resynthesizes output power back to perfect sine wave AC with enhanced protection from harmonic distortion, fast electrical impulses and other hard-to-solve power problems not addressed by other UPS types. Highly efficient operation in optional economy mode significantly reduces BTU heat output and operating energy costs. Network-grade AC surge and noise suppression. Supports detailed monitoring of equipment load levels, self-test data and utility power conditions via built-in RS-232 and USB interfaces. Optional SNMP/Web and contact-closure communications card accessories available. HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X. Included PowerAlert monitoring software offers detailed site power and UPS updates with support for safe auto-shutdown of connected systems as UPS batteries become depleted. Included software packages include PowerAlert Local, PowerAlert Network Shutdown Agent and PowerAlert Network Management System for complete support for a wide variety of application types. Supports Emergency Power Off (EPO) via built-in interface. Front panel LEDs and LCD readout with scroll controls support front-panel visual monitoring of all major UPS functions with support for a variety of control options to support advanced UPS settings and configurations. LED / LCD display panel rotates for viewing in rackmount or tower configurations. L6-30P input, plus 2 L6-30R, 2 L6-20R and 12 5-15/20R outlets. External battery packs are field replaceable and hot swappable. 2 year warranty and \$250,000 connected equipment insurance; extended warranty and service contracts available.

#### Features

- Tripp Lite E-series SU5000RT4UTF 5000VA / 5kVA / 4500 watt on-line, double-conversion UPS system in a 6U rack/tower configuration

(4U UPS power module with internal batteries + 2U step-down transformer)

- Full-time active power conditioning maintains clean, continuous dual-conversion AC output free of voltage fluctuations, power interruptions and line noise
- Fault-tolerant auto-bypass prevents unexpected service interruptions during UPS overload or fault conditions
- L6-30P input plug, plus 2 L6-30R, 2 L6-20R and 12 5-15/20R outlets
- Included rail kits support rackmount installation of both included modules in 4 post racks
- Optional 2POSTRMKITHD supports installation in 2 post 19 inch racks (2 required for SU5000RT4UTF)
- Optional 2-9USTAND supports upright tower placement (1 required for SU5000RT4UTF)
- Maximum installed rack depth of only 20.75 in. / 52.7 cm
- Maintains full-time sine wave output within 2% of 208V & 120V nominal in double conversion mode
- Corrects brownouts to 156V at full load (100V at 50% load or less)
- Corrects overvoltages to 290V at full load (300V at 90% load or less)
- Double-conversion operation offers full-time AC to DC, then DC to AC conversion to maintain perfectly regulated sine wave AC output with enhanced protection from harmonic distortion, fast electrical impulses and other hard-to-solve power problems not addressed by other UPS types
- High efficiency ECONOMY MODE operation significantly reduces BTU heat output and operating energy costs
- Network-grade AC surge and noise suppression
- Supports detailed monitoring of equipment load levels, self-test data and utility power conditions via built-in RS-232, USB and optional SNMP card slot interfaces
- UPS card slot supports one card-based network interface option (part # SNMPWEBCARD) or dry-contact monitoring accessory (part # RELAYIOCARD)
- Optional SNMPWEBCARD offers communications and control via secure remote web and network interfaces
- Optional RELAYIOCARD supports six configurable hard contact closure outputs for custom event notification
- Optional RELAYIOMINI interface module offers three configurable hard contact closure outputs for custom event notification (requires removal of USB interface module)
- HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X
- Includes Free PowerAlert monitoring software packages; PowerAlert LOCAL for desktops and small business networks, PowerAlert NSA (Network Shutdown Agent) for larger networks and PowerAlert NMS (Network Management System) for monitoring up to 250 SNMP-enabled UPS, PDU and other networking devices
- Front panel LEDs and LCD readout with scroll controls support front-panel visual monitoring of all major UPS functions with support for a variety of control options to support advanced UPS settings and configurations
- LED/LCD display panel rotates for viewing in rackmount or tower configurations
- Supports Emergency Power Off (EPO) via built-in interface
- Battery independent restart ensures automatic UPS power-up without user interaction after lengthy power outages, even when batteries are expired and require replacement
- External battery packs are field replaceable and hot swappable
- 2-year warranty and \$250,000 connected equipment insurance; extended warranty and service contracts available

## Specifications

OUTPUT	
Output Volt Amp Capacity (VA)	5000
Output kVA capacity (kVA)	5.0
Output Watt Capacity (watts)	4500
Output kW capacity	4.5
Output power factor	0.9
Crest Factor	3:1
Nominal Output Voltage(s) Supported	120V; 208V
Frequency compatibility	60 Hz

<b>Output voltage regulation (line mode)</b>	+/- 2%
<b>Output voltage regulation (Economy line mode)</b>	+/- 10%
<b>Output voltage regulation (Battery mode)</b>	+/- 2%
<b>Built-in UPS output receptacles</b>	12 5-15/20R outlet(s); 2 L6-20R outlet(s); 2 L6-30R outlet(s)
<b>Output circuit breaker</b>	High voltage 20A breaker protects L6-20R outlets, L6-30R outlets are unbreakered; Low voltage 20A breakers protect 3 5-15/20R outlets each
<b>Basic PDU options</b>	<a href="#">PDU1220</a> (1U / 13 5-15/20R outlets); <a href="#">PDU1230</a> (1U / 2 C19, 16 C13 outlets); <a href="#">PDUNV</a> (1U / 2 C19, 12 C13 outlets); <a href="#">PDUV20</a> (0U / 12 5-15/20R outlets); <a href="#">PDU40TDUAL</a> (0U / 40 5-15/20R outlets); <a href="#">PDUV30HV</a> (0U / 6 C19, 32 C13 outlets)
<b>Metered PDU options</b>	<a href="#">PDUMH20</a> (1U / 13 5-15/20R outlets); <a href="#">PDUMH20AT</a> (1U / 16 5-15/20R outlets)*; <a href="#">PDUMV20</a> (0U / 16 5-15/20R outlets); <a href="#">PDUMV40</a> (0U / 32 5-15/20R outlets); <a href="#">PDUMV20HV</a> (0U / 6 C19, 32 C13 outlets); <a href="#">PDUMV30HV</a> (0U / 6 C19, 24 C13 outlets)
<b>Monitored PDU options</b>	<a href="#">PDUMNV20</a> (0U / 24 5-15/20R outlets); <a href="#">PDUMNV20HV</a> (0U / 4 C19, 20 C13 outlets); <a href="#">PDUMNV30HV</a> (0U / 4 C19, 20 C13 outlets); <a href="#">PDUMNH20</a> (1U / 16 5-15/20R outlets)
<b>Switched PDU options</b>	<a href="#">PDUMH20ATNET</a> (1U / 16 5-15/20R outlets)*; <a href="#">PDUMH20HVNET</a> (1U / 8 C13 outlets); <a href="#">PDUMH30HVNET</a> (2U / 16 C13 outlets); <a href="#">PDUMV20NET</a> (0U / 24 5-15/20R outlets); <a href="#">PDUMV20HVNET</a> (0U / 4 C19, 24 C13 outlets); <a href="#">PDUMV30HVNET</a> (0U / 4 C19, 24 C13 outlets)
<b>Output AC waveform (AC mode)</b>	Pure sine wave
<b>Output AC waveform (battery mode)</b>	Pure Sine wave
<b>INPUT</b>	
<b>Rated input current (at maximum load)</b>	24A (208V)
<b>Nominal Input Voltage(s) Supported</b>	208V AC
<b>UPS input connection type</b>	L6-30P
<b>UPS Input cord length (ft.)</b>	10
<b>UPS Input cord length (m)</b>	3
<b>Recommended Electrical Service</b>	30A
<b>BATTERY</b>	
<b>Full load runtime (minutes)</b>	3.5 minutes (4500w)
<b>Half load runtime (minutes)</b>	11 minutes (2250w)
<b>Expandable battery runtime</b>	Supports extended runtime with optional external battery packs
<b>External battery pack compatibility</b>	<a href="#">BP192V12-3U</a>

<b>DC system voltage (VDC)</b>	192
<b>Battery recharge rate (included batteries)</b>	6 hours (from 10% to 90%)
<b>Replacement battery cartridge (internal UPS battery replacement)</b>	<a href="#">RBC5-192</a> (qty 1)
<b>Battery Access</b>	Front panel battery access door
<b>Battery replacement description</b>	Hot-swappable, user replaceable batteries
<b>VOLTAGE REGULATION</b>	
<b>Voltage regulation description</b>	Online, double-conversion power conditioning
<b>Overvoltage correction</b>	2% output voltage regulation during overvoltages to 280V (full load) / 300V (90% load or less)
<b>Undervoltage correction</b>	2% output voltage regulation during undervoltages to 156V (full load) / 100V (50% load or less)
<b>LEDS ALARMS &amp; SWITCHES</b>	
<b>LED Indicators</b>	6 LEDs indicate line power, online mode, economy/bypass mode, on-battery, charger and AC output status; LCD screen offers additional information and control options
<b>Front panel LCD display</b>	Selectable LCD display with scroll and selection buttons enables UPS control and detailed monitoring options; LED/LCD panel rotates for viewing in rack/tower formats (see manual)
<b>Alarms</b>	Unique audible alarms for all major UPS, environmental and power conditions (see manual)
<b>Alarm cancel operation</b>	Alarm cancel switch
<b>Switches</b>	2 Switches control off/on power status and alarm-cancel/self-test operation; 2 additional switches support set and execute scrolling LCD functions
<b>SURGE / NOISE SUPPRESSION</b>	
<b>UPS AC suppression response time</b>	Instantaneous
<b>EMI / RFI AC noise suppression</b>	Yes
<b>PHYSICAL</b>	
<b>Installation form factors supported with included accessories</b>	4 post 19 inch rackmount (mounting kit included)
<b>Included mounting accessory description</b>	2 sets of adjustable 4 post rack rails included
<b>Installation form factors supported with optional accessories</b>	2 post rackmount (2POSTRMKITWM); Tower (2-9USTAND)
<b>Optional mounting accessory notes</b>	2 sets of <a href="#">2POSTRMKITHD</a> required for 2 post rackmount installation of separate 4U power module and 2U transformer
<b>Primary form factor</b>	Rackmount

<b>UPS / Power Module dimensions in primary form factor (height x width x depth / inches)</b>	6.85 x 17.5 x 20.7
<b>UPS / Power Module dimensions in primary form factor (height x width x depth / cm)</b>	17.4 x 44.5 x 52.6
<b>Installed whole system maximum rack depth (inches)</b>	20.75
<b>Installed whole system maximum rack depth (cm)</b>	52.7
<b>Installed whole system total rack space height (rack spaces)</b>	6U
<b>Secondary form factor</b>	Tower
<b>UPS / Power Module weight (lbs)</b>	113.6
<b>UPS / Power Module weight (kg)</b>	51.6
<b>Stepdown transformer dimensions (height x width x depth / inches)</b>	3.5 x 17.5 x 20.75
<b>Stepdown transformer dimensions (height x width x depth / cm)</b>	8.8 x 44.4 x 52.7
<b>Stepdown transformer weight (lbs)</b>	76
<b>Stepdown transformer weight (kg)</b>	34.5
<b>UPS Shipping dimensions (height x width x depth / inches)</b>	22 x 25 x 30
<b>UPS Shipping dimensions (height x width x depth / cm)</b>	55.9 x 63.5 x 76.2
<b>Shipping weight (lbs)</b>	278
<b>Shipping weight (kg)</b>	126.2
<b>UPS housing material</b>	Sheet metal
<b>Cooling method</b>	Fan
<b>ENVIRONMENTAL</b>	
<b>Operating Temperature Range</b>	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius

<b>Storage Temperature Range</b>	5 to 122 F / -15 to 50 C
<b>Relative Humidity</b>	5% to 90% (non-condensing)
<b>AC mode BTU / hr. (full load)</b>	1767
<b>AC economy mode BTU / hr. (full load)</b>	638
<b>Battery mode BTU / hr. (full load)</b>	1700
<b>AC economy mode efficiency rating (100% load)</b>	96%
<b>Operating Elevation (ft)</b>	0 to 6560 ft. / 0 to 2000 m
<b>Audible Noise</b>	65 dB at 1m front side
<b>COMMUNICATIONS</b>	
<b>Communications interface</b>	USB (HID enabled); DB9 Serial; Contact closure; EPO (emergency power off); Slot for SNMP/Web interface
<b>Network monitoring port description</b>	Two contact closure monitoring options available - RELAYIOCARD with six configurable contact closure outputs (uses UPS card slot) and RELAYIOMINI with 3 configurable contact closure outputs (requires removal of USB port module)
<b>PowerAlert software</b>	Included
<b>Communications cable</b>	USB, DB9 serial and EPO cables included
<b>WatchDog compatibility</b>	Yes
<b>LINE / BATTERY TRANSFER</b>	
<b>Transfer time</b>	No transfer time (0 ms.) in online, double-conversion mode
<b>Low voltage transfer to battery power (setpoint)</b>	156V (full load) / 100V (50% load or less, derates linearly)
<b>High voltage transfer to battery power (setpoint)</b>	280V (full load) / 300V (90% load or less)
<b>SPECIAL FEATURES</b>	
<b>Cold Start (startup in battery mode during a power failure)</b>	Cold-start operation supported
<b>High availability UPS features</b>	Automatic inverter bypass; Hot swappable batteries
<b>Green &amp; high efficiency features</b>	High efficiency economy mode operation; Support for daily startup and shutoff; Schedulable daily hours of economy mode operation
<b>CERTIFICATIONS</b>	
<b>UPS Certifications</b>	Tested to UL1778 (USA); Tested to CSA (Canada); Meets FCC Part 15 Category B (EMI); ROHS (Restriction of Hazardous Substances)
<b>UPS Certification details</b>	IEC 61000-4-5 1995 B Surge Immunity
<b>WARRANTY</b>	

<b>Product Warranty Period (U.S., Canada &amp; Puerto Rico)</b>	2 years
<b>Connected Equipment Insurance (U.S., Canada &amp; Puerto Rico)</b>	\$250,000 connected equipment insurance

## Related Items

### Optional Products

Product Type	Related Model	Description	Qty.
External Battery Packs	<a href="#">BP192V12-3U</a>	BP192V12-3U - External Battery Pack for UPS System	-
Tower Stands	<a href="#">2-9USTAND</a>	Enables Tower Placement of Rackmount UPS Systems	-
SNMP Accessories	<a href="#">SNMPWEBCARD</a>	For remote monitoring and control via SNMP, Web, or Telnet.	-
UPS Accessories	<a href="#">RELAYIOCARD</a>	Programmable Relay I/O Card	-
Environmental Monitoring	<a href="#">ENVIROSENSE</a>	Monitors temperature, humidity and contact-closure inputs. (Requires SNMPWEBCARD or switched PDU.)	-
Extended Warranties	<a href="#">WEXT3-SU5000HV</a>	3-Year Extended Warranty - For SU5000RT3UHV UPS only	-
Extended Warranties	<a href="#">WEXT5-SU5000HV</a>	5-Year Extended Warranty - For SU5000RT3UHV UPS only	-
UPS Accessories	<a href="#">RELAYIOMINI</a>	3 Relay I/O Mini-module	-
Rackmount/Wallmount Kits	<a href="#">2POSTRMKITHD</a>	Enables 2-Post Rackmount Installation of 3U and Larger UPS, Transformer and Battery Pack Components	-

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=4529](http://www.tripplite.com/en/products/model.cfm?txtModelID=4529).

Copyright © 2010 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.