



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SU750XL

### SmartOnline Expandable Tower UPS System - On-line, double-conversion protection for mission-critical applications



#### Highlights

- 750VA/600W on-line expandable runtime tower UPS system
- HID-compliant USB port, serial port and SNMP/WEB card slot
- Maintains 120V +/-2% output during overvoltages to 150V and brownouts as low as 65V
- NEMA 5-15P (120V 15A) input plug, 6 x NEMA 5-15R outlets, two individually controllable single-outlet load banks
- Fault-tolerant auto-bypass
- \$250,000 [Ultimate Lifetime Insurance](#) (USA & Canada only)

#### Description

The SU750XL on-line, double-conversion UPS protects critical server, networking or telecommunications equipment from blackouts, brownouts, voltage fluctuations and surges. Large-capacity 750VA/600W UPS continuously converts incoming AC to DC, then back to perfect sine wave AC output at 120V AC (+/-2%). Removes harmonic distortion, fast electrical impulses, frequency fluctuations and other hard-to-solve power problems not addressed by other UPS systems. True sine wave output and zero transfer time offer guaranteed compatibility with all equipment types. Includes 6 UPS supported outlets; 2 single-outlet load banks can be independently controlled via a software interface to selectively reboot remote equipment or shed less critical loads to extend battery runtime for the most critical equipment. Extended runtime available with optional BP24V15RT2U, BP24V28-2U, or BP24V70-3U external battery packs. Includes slot for internal SNMP/WEB card, plus DB9 enhanced serial monitoring port for unattended shutdown, remote control and monitoring of UPS system and power data. Includes USB and DB9 serial ports. Built-in DB9 port offers both enhanced RS-232 enabled monitoring data, plus contact closure monitoring ability. HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X. Includes Tripp Lite's PowerAlert UPS power management software. Compatible with Tripp Lite's Watchdog service monitoring/rebooting software. Upright tower form factor; attractive all-black color scheme.

#### Package Includes

- SU750XL UPS System
- PowerAlert Software CD and cabling
- EPO (Emergency Power Off) cabling
- Owner's manual with warranty information

#### Features

- True on-line, double-conversion UPS provides constant, pure sine wave AC output
- Maintains continuous operation with zero transfer time through blackouts, brownouts, voltage fluctuations and surges
- Removes harmonic distortion, electrical impulses, frequency variations and other hard-to-solve power problems
- Accepts input voltages between 80-150V (65-150V at loads under 70%), regulating output to 120V AC +/-2%
- 750VA/600W output capacity with 6 x NEMA5-15R outlets
- Two built-in individually switchable load banks can be controlled via software interface to selectively reboot remote equipment or shed less critical loads to extend battery runtime for the most critical equipment (1 outlet per bank)
- Standard internal battery set provides 11 min. runtime at half load and 4 min. at full load

- Extended runtime available with optional BP24V15RT2U, BP24V28-2U, or BP24V70-3U external battery packs
- HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X
- DB9 serial network interface supports RS-232 and contact closure messaging
- Slot for optional SNMP/WEB card (part# SNMPWEBCARD)
- Included PowerAlert UPS power management software and cabling provides monitoring of in-depth site power conditions, full UPS status and fault warnings, output load level and load bank power control
- Compatible with Tripp Lite's WatchDog service monitoring/rebooting software (part# WATCHDOGSW)
- Fault-tolerant auto-bypass maintains continuous utility output to connected equipment, even in cases where the UPS is overloaded or suffers an internal failure that requires service
- Diagnostic LEDs
- Upright tower format; attractive all-black color scheme
- \$250,000 Ultimate Lifetime [connected equipment insurance](#) (USA & Canada only)
- 2-year warranty

## Specifications

OUTPUT	
Output Volt Amp Capacity (VA)	750
Output Watt Capacity (watts)	600
Output power factor	0.8
Crest Factor	3:1
Nominal Output Voltage(s) Supported	100V; 110V; 120V
Nominal Voltage details	120V default
Frequency compatibility	50 / 60 Hz
Frequency compatibility details	Output frequency matches input nominal on startup, defaults to 60 Hz on cold-start
Output voltage regulation (line mode)	+/- 2%
Output voltage regulation (Battery mode)	+/- 2%
Built-in UPS output receptacles	6 5-15R outlet(s)
Built-in controllable switched load banks	Two switchable single-outlet 5-15R load banks
Basic PDU options	<a href="#">PDU1215</a> (1U / 13 5-15R outlets); <a href="#">PDUNV</a> (1U / 2 C19, 12 C13 outlets); <a href="#">PDU1415</a> (0U / 14 5-15R outlets); <a href="#">PDUV15</a> (0U / 12 5-15R outlets)
Metered PDU options	<a href="#">PDUMH15</a> (1U / 13 5-15R outlets); <a href="#">PDUMH15AT</a> (1U / 8 5-15R outlets)*; <a href="#">PDUMV15</a> (0U / 16 5-15R outlets)
Switched PDU options	<a href="#">PDUMH15ATNET</a> (1U / 8 5-15R outlets)*; <a href="#">PDUMV15NET</a> (0U / 16 5-15R outlets)
External PDU redundancy options	*ATS switch options <a href="#">PDUMH15AT</a> & <a href="#">PDUMH15ATNET</a> support dual UPS and hot-swappable UPS configurations
Output AC waveform (AC mode)	Sine wave
Output AC waveform (battery mode)	Sine wave
INPUT	

Rated input current (at maximum load)	6.2A
Nominal Input Voltage(s) Supported	100V AC; 110V AC; 120V AC
UPS input connection type	5-15P
Input circuit breaker	15A
UPS Input cord length (ft.)	10
UPS Input cord length (m)	3
Recommended Electrical Service	15A 120V
<b>BATTERY</b>	
Full load runtime (minutes)	4 min. (600w)
Half load runtime (minutes)	11 min. (300w)
External battery pack compatibility	<a href="#">BP24V15RT2U</a> (limit 1); <a href="#">BP24V28-2U</a> (limit 1); <a href="#">BP24V70-3U</a> (multi-pack compatible)
DC system voltage (VDC)	24
Battery recharge rate (included batteries)	Less than 6 hours from 10% to 90%
Replacement battery cartridge (internal UPS battery replacement)	<a href="#">RBC24-SUTWR</a>
Battery Access	Battery access door
Battery replacement description	Hot-swappable, user replaceable batteries
<b>VOLTAGE REGULATION</b>	
Voltage regulation description	Online, double-conversion power conditioning
Overvoltage correction	2% output voltage regulation during overvoltages to 150
Undervoltage correction	2% output voltage regulation during undervoltages to 80
Severe undervoltage correction	2% output voltage regulation during undervoltages to 65 (under 70% load only)
<b>LEDS ALARMS &amp; SWITCHES</b>	
LED Indicators	14 LEDs indicate line power, online mode, bypass mode, on-battery, overload, battery low, replace battery and fault status information - includes 4-LED meter display for load and battery charge level
Alarms	Audible alarm indicates UPS startup, power-failure, low-battery, overload, UPS fault and remote shutdown conditions
Alarm cancel operation	Power-fail alarm can be silenced using alarm-cancel switch
Switches	2 Switches control off/on power status and alarm-cancel/self-test operation
<b>SURGE / NOISE SUPPRESSION</b>	

UPS AC suppression joule rating	570
UPS AC suppression response time	Instantaneous
UPS Dataline suppression	1 line TEL / DSL or 10Base T Ethernet protection
EMI / RFI AC noise suppression	Yes
<b>PHYSICAL</b>	
Installation form factors supported with included accessories	Tower
Primary form factor	Tower
UPS / Power Module dimensions in primary form factor (height x width x depth / inches)	10 x 6.8 x 13.2
UPS / Power Module dimensions in primary form factor (height x width x depth / cm)	25.4 x 17.1 x 33.7
UPS / Power Module weight (lbs)	28.7
UPS / Power Module weight (kg)	13
UPS Shipping dimensions (height x width x depth / inches)	14.2 x 10 x 18.5
UPS Shipping dimensions (height x width x depth / cm)	36.2 x 25.4 x 47
Shipping weight (lbs)	34.2
Shipping weight (kg)	15.5
UPS housing material	Steel
Cooling method	Fan
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
Storage Temperature Range	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
Relative Humidity	0 to 95%, non-condensing
AC mode BTU / hr. (full load)	304.8
Battery mode BTU / hr. (full load)	304.8
Audible Noise	< 45 dB at front side 1m
<b>COMMUNICATIONS</b>	

<b>Communications interface</b>	USB (HID enabled); DB9 Serial; Contact closure; EPO (emergency power off); Slot for SNMP/Web interface
<b>Network monitoring port description</b>	Supports detailed monitoring of UPS and site power conditions; DB9 port supports RS232 and contact closure communications
<b>PowerAlert software</b>	Included
<b>Communications cable</b>	USB and DB9 cabling included
<b>WatchDog compatibility</b>	Supports Watchdog application, OS and hard-reboot restart options for remote applications
<b>LINE / BATTERY TRANSFER</b>	
<b>Transfer time</b>	No transfer time (0 ms.) in online, double-conversion mode
<b>Low voltage transfer to battery power (setpoint)</b>	80V (100% load), 65V (
<b>High voltage transfer to battery power (setpoint)</b>	150
<b>SPECIAL FEATURES</b>	
<b>Cold Start (startup in battery mode during a power failure)</b>	Cold-start operation supported
<b>High availability UPS features</b>	Automatic inverter bypass; Hot swappable batteries
<b>Green &amp; high efficiency features</b>	Individually controllable load banks
<b>CERTIFICATIONS</b>	
<b>UPS Certifications</b>	Tested to UL1778 (USA); Tested to CSA (Canada); Meets FCC Part 15 Category B (EMI); Meets FCC Part 68 / Industrie Canada (telecommunications); ROHS (Reduction of Hazardous Substances)
<b>WARRANTY</b>	
<b>Product Warranty Period (U.S., Canada &amp; Puerto Rico)</b>	2 years
<b>Connected Equipment Insurance (U.S., Canada &amp; Puerto Rico)</b>	\$250,000 connected equipment insurance

## Related Items

### Optional Products

Product Type	Related Model	Description	Qty.
SNMP Accessories	<a href="#">SNMPWEBCARD</a>	For remote monitoring and control via SNMP, Web, or Telnet.	-
SNMP Accessories	<a href="#">ENVIROSENSE</a>	Monitors temperature, humidity and contact-closure inputs. (Requires SNMPWEBCARD or switched PDU.)	-
UPS Accessories	<a href="#">RELAYIOCARD</a>	Programmable Relay I/O Card	-
UPS Accessories	<a href="#">MODBUSCARD</a>	For remote monitoring and control via MODBUS protocol	-
Shutdown Cable Kits	<a href="#">AS400CABLE KIT</a>	Power Management Tools - UPS Communication Cable Kit for System i / AS400 / iSeries Servers	-
External Battery Packs	<a href="#">BP24V15RT2U</a>	BP24V15RT2U - External Battery Pack for UPS System	-
External Battery Packs	<a href="#">BP24V28-2U</a>	BP24V28-2U - External Battery Pack for UPS System	-
External Battery Packs	<a href="#">BP24V70-3U</a>	BP24V70-3U - External Battery Pack for UPS System	-

Extended Warranties	<a href="#">WEXT3-500-1500</a>	3-Year Extended Warranty - For Smart Line-Interactive and Online Tower or Rack models, 1500VA or less	-
Extended Warranties	<a href="#">WEXT5-500-1500</a>	5-Year Extended Warranty - For Smart Line-Interactive and Online Tower or Rack models, 1500VA or less	-
Power Distribution	<a href="#">PDU1215</a>	Basic PDU / Power Distribution Unit - Safe, reliable power distribution for critical networking equipment	-
Power Distribution	<a href="#">PDUB15</a>	Dual source Power Distribution Unit / PDU with Manual Transfer Switch enables Hot-swappable UPS Replacement in Critical Network Applications	-
Power Distribution	<a href="#">PDUV15</a>	Safe, reliable power distribution for critical networking equipment	-
Power Distribution	<a href="#">PDUNV</a>	Basic PDU / Power Distribution Unit - Safe, reliable power distribution for critical networking equipment	-
Power Distribution	<a href="#">PDUMH15</a>	Metered PDU / Power Distribution Unit - Safe, reliable power distribution with digital current meter	-
Power Distribution	<a href="#">PDUMV15</a>	Metered PDU / Power Distribution Unit - Safe, reliable power distribution with digital current meter	-
Power Distribution	<a href="#">PDUMH15AT</a>	Metered PDU with ATS - Power Distribution Unit with dual-input Auto Transfer Switching	-
Power Distribution	<a href="#">PDUMNH15</a>	Monitored PDU / Power Distribution Unit supports real-time remote monitoring of load level, voltage and frequency with options for remote environmental and security monitoring	-
Power Distribution	<a href="#">PDUMNV15</a>	Monitored PDU / Power Distribution Unit supports real-time remote monitoring of load level, voltage and frequency with options for remote environmental and security monitoring	-
Power Distribution	<a href="#">PDUMH15ATNET</a>	Switched, Metered PDU with ATS - Power Distribution Unit with dual-input Auto Transfer Switching, individual outlet control and remote network interface	-
Power Distribution	<a href="#">PDUMV15NET</a>	Switched, Metered PDU with Remote Monitoring - 0U Vertical Rackmount Power Distribution Unit for Networks with Individually Switchable Outlets, Current Metering, Remote Monitoring and Control	-
Power Cables	<a href="#">P007-002</a>	2-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	-
Power Distribution	<a href="#">P007-006</a>	6-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	-
Power Cables	<a href="#">P007-010</a>	10-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	-
Power Cables	<a href="#">P010-012</a>	12-ft. 18AWG Power cord (NEMA 5-15P to IEC-320-C13)	-
Power Distribution	<a href="#">P022-001</a>	1-ft. 18AWG Power Extension cord (NEMA 5-15R to NEMA 5-15P)	-
Power Cables	<a href="#">P023-001</a>	1-ft. 14AWG Power Adapter cord (NEMA L5-15R to NEMA 5-15P)	-
Power Cables	<a href="#">P034-010</a>	10-ft. 14AWG Heavy Duty Power cord ( IEC-320-C19 to NEMA 5-15P)	-

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=3299](http://www.tripplite.com/en/products/model.cfm?txtModelID=3299).

Copyright © 2010 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.