



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SU8000RT3UPM

SmartOnline 8000VA Power Module - Hot-swappable power module for redundant power applications



Highlights

- 8000VA on-line 3U rack/tower hot-swappable power module
- Ideal for use as a spare or redundant power module for mission-critical UPS configurations involving SU8000RT3U or SU8000RT3U1TF

Description

8,000 VA (8kVA) on-line, double-conversion UPS power module for spare or redundant UPS configurations involving SU8000RT3U, SU8000RT3U1TF, SU7500RT3U or SU7500RT3U1TF UPS bundles. POWER MODULE ONLY.

Package Includes

- SU8000RT3UPM POWER MODULE ONLY (3u)

Features

- 8,000VA (8kVA) on-line, double-conversion UPS power module for spare or redundant UPS configurations involving SU8000RT3U, SU8000RT3U1TF, SU7500RT3U or SU7500RT3U1TF UPS bundles.
- POWER MODULE ONLY

Specifications

OVERVIEW	
Model Type	Power Modules
OUTPUT	
Output Volt Amp Capacity (VA)	8000
Output kVA capacity (kVA)	8
Output Watt Capacity (watts)	7200
Output kW capacity	7.2
Output power factor	0.9
Crest Factor	3:1

Nominal Output Voltage(s) Supported	200V; 208V; 220V; 230V; 240V
Frequency compatibility	50 / 60 Hz
Output AC waveform (AC mode)	Sine wave
Output AC waveform (battery mode)	Sine wave
INPUT	
Nominal Input Voltage(s) Supported	200V AC; 208V AC; 220V AC; 230V AC; 240V AC
LEDS ALARMS & SWITCHES	
Front panel LCD display	Selectable LCD display with scroll and selection buttons enables UPS control and detailed monitoring options; LED/LCD panel rotates for viewing in rack/tower formats (see manual)
Alarms	Unique audible alarms for all major UPS, environmental and power conditions (see manual)
Alarm cancel operation	Alarm cancel switch
Switches	2 Switches control off/on power status and alarm-cancel/self-test operation; 2 additional switches support set and execute scrolling LCD functions
PHYSICAL	
Primary form factor	Rackmount
UPS / Power Module dimensions in primary form factor (height x width x depth / inches)	5.14 x 17.5 x 25.82
UPS / Power Module dimensions in primary form factor (height x width x depth / cm)	13.1 x 44.4 x 65.6
UPS / Power Module weight (lbs)	43
UPS / Power Module weight (kg)	19.5
UPS dimensions details	3U power module component only
UPS Shipping dimensions (height x width x depth / inches)	9.7 x 23.6 x 39.4
UPS Shipping dimensions (height x width x depth / cm)	24.6 x 59.9 x 100.1
Shipping weight (lbs)	66
Shipping weight (kg)	30
UPS housing material	Steel
COMMUNICATIONS	
Communications interface	USB (HID enabled); DB9 Serial; EPO (emergency power off); Slot for SNMP/Web interface
CERTIFICATIONS	
UPS Certifications	Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico); Tested to CE (EU); Meets FCC Part 15 Category A (EMI); ROHS (Reduction of Hazardous Substances)

WARRANTY**Product Warranty
Period (U.S., Canada &
Puerto Rico)**

2 years

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3553.

Copyright © 2010 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.