

BP192V12-3U

External Battery Pack for UPS Systems



Model #: BP192V12-3U

- ▶ Extends runtime of compatible Tripp Lite UPS Systems with 192VDC external battery connection
- ▶ Provides daisy-chain capability
- ▶ Simple installation; 3U rackmount, tower or stack adaptable
- ▶ 2-year warranty

DESCRIPTION

Tripp Lite's BP192V12-3U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite UPS systems. Multi-use form factor supports configuration in rackmount or stacking applications using only 3 rack spaces (3U). Upright tower configuration supported with optional 2-9USTAND accessory. Includes heavy-gauge cabling with high-current DC connectors for simple installation. Additional output connector allows multiple BP192V12-3U battery packs to be daisy-chained to the UPS for even longer extended run operation.

COMPATIBLE UPS SYSTEMS - SU5000RT4U, SU6000RT4U and other Tripp Lite UPS systems that specify the use of this battery pack.

KEY BUYING POINTS

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 3 rack spaces (3U)
- Supports upright tower installation with optional 2-9USTAND accessory (holds 3 battery packs in tower configuration)
- Set of two input/output connectors allows multiple BP192V12-3U battery packs to be daisy-chained to the UPS for even longer extended run operation
- Includes heavy-gauge cabling with high-current DC connectors for simple installation
- 2-year warranty

TYPICAL APPLICATIONS

- Ideal means of lengthening the battery runtime provided by compatible Tripp Lite UPS systems. Additional battery packs may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired.

OPTIONS & ACCESSORIES

- Tower stands: [2-9USTAND](#)
- Extended Warranties: 3 year [WEXT3-BP240V10](#), 5 year [WEXT5-BP240V10](#)

PACKAGE INCLUDES

- BP192V12-3U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

COMPLETE SPECIFICATIONS

OUTPUT

Overload protection: 50A DC output fuse

INPUT

Input cord length: 36 in./9m, 8 AWG, 3 conductor

BATTERY

Expandable battery runtime: Includes a second input/output connector to daisy-chain multiple battery packs

DC system voltage: 192VDC

Typical battery lifespan: 4-6 years typical (North America)

Connects to UPS via: Detachable cable with UPS specific DC connector (90 cm length, 8 gauge)

PHYSICAL

Shipping weight (lbs): 211.25

Shipping weight (kg): 95.9

Unit weight (lbs): 174

Unit weight (kg): 79

Unit Dimensions (HWD/in): 5.25 x 17.5 x 28

Unit Dimensions (HWD/cm): 13.3 x 44.5 x 71.1

Shipping Dimensions (HWD/in): 11.25 x 31.5 x 23

Shipping Dimensions (HWD/cm): 28.6 x 80 x 58.4

Material of construction: Black steel cabinet

Form factors supported: Stacking upright tower and 3U rackmount form factors supported

WARRANTY

Optional coverage: 3 year, 5 year, next day and on-site warranty coverage available

Product warranty: 2-year product warranty

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



© 2006 Tripp Lite. All Rights Reserved.